

HEAVY DUTY FAN



1xø4"



2xø4"



3xø4"

LINK Heavy Duty Fan Features

- Fan's type designed to 4" with heavy duty 2 ball bearing.
- Impellers made from fiberglass reinforced plastic, UL94V-0 rating
- 120x120x38mm Die-Cast Aluminum Housing.
- 7.0mm ABS Plastic Guard with trademark embossing.
- 220VAC with grounding system for 2x4" & 3x4"
- Black frame made from Electro-Galvanized Steel with Electrostatic powder coating process.

Technical Specifications

- Speed : 2,650 rpm @ 50 Hz, 3,000 rpm @ 60 Hz
- Max Air Flow : 2.38 m³/min or 84.8 CFM
- Operating Temp : -30°C to 70°C
- Input Voltage : 220 - 230 VAC, 50/60 Hz
- Max Power :
 - 1xø4" : 22Watts @ 50Hz, 19 Watts @ 60Hz
 - 2xø4" : 44Watts @ 50Hz, 38 Watts @ 60Hz
 - 3xø4" : 66Watts @ 50Hz, 57 Watts @ 60Hz
- Acoustical Noise : 46 dB
- Life expectancy : 50,000 Hours
- Power cord : 1.8m (2x0.5mm²) for CK-80104, 1.4m (3x18 AWG) for CK-81204 and CK-81304
- Approvals : CE & UL/CSA

Ordering information

Order Number	Description	Power Cord
CK-80104	FAN 1xø4" HEAVY DUTY FAN	1.8 m.
CK-81204	FAN 2xø4" HEAVY DUTY FAN	1.4 m.
CK-81304	FAN 3xø4" HEAVY DUTY FAN	1.4 m.