

WAVE WALL RACK



Mounting Pole

Rack Unit (U) Screen on Pole



Side Panel

Easy to Remove by Slide Lock and Security Lock



Single Part



Double Part



Security Lock

Press and Swing Handle Lock



Grounding System

Connected between cabinet's structure and front door with copper ground wire 2.5mm²

LINK Wave Wall Rack Features

- Suitable for indoor installation (Wall mount type) designed in front door, central panel and back base. Central panel equipped with rollers for opening and locking to back base part (excluding for 40cm depth).
- Cabinet made from 1.2mm Electro-Galvanized Steel Sheet and 2.0mm for 4-Mounting pole.
- Front door designed in hexa perforated for ventilation, swing handle lock was provided.
- Back part with hanger slots (steel frame) and provided 4 sets of wall mounting screw.
- Mounting pole can be adjustable with screened Rack Unit (U) on the pole.
- Cable access at the top and the base.
- Raised roof with vented and perforated surrounding for ventilation, can be mounted maximum 3 ventilating fans.
- Provided nuts and screws according to no. of Rack unit (U) for convenience to install network equipment.
- Both side panels are easy to open by slide lock and provided security lock for installation and maintenance.
- 180° opening door and can change the opening direction.
- Grounding system connected between cabinet's structure and front door.
- Supplementary accessories: shelves, drawers, fan sets, power distribution unit.

Standards

- 19" Standard, ISO9001:2015 and ISO14001 : 2015
- ANSI/EIA-310D, IEC60297-1, IEC60297-2, BS5954 Part : 2, DIN 41494

Specifications

Material

- Frame : 1.2 mm Electro-galvanized steel sheet
- Rear and Side Panels : 1.2 mm Electro-galvanized steel sheet
- Solid blanking plate : 1.2 mm Electro-galvanized steel sheet
- Wave Perforated Door : 1.2 mm Electro-galvanized steel sheet
- Mounting Pole : 2.0 mm Electro-galvanized steel sheet with Zinc coated

Surface Finishing

- Electrostatic powder coating, Black (RAL9004)

Scope of Delivery

- Cabinets are packed in cartons.

Ordering information

U Height (U=4.45 cm.)	Width (cm.)	Depth		Height (cm.)	Order Number
		(cm.)	(Part)		
6U	60	40	Single	37	CW1-60406W
	60	50	Double	37	CW2-60506W
	60	60	Double	37	CW2-60606W
9U	60	40	Single	50.5	CW1-60409W
	60	50	Double	50.5	CW2-60509W
	60	60	Double	50.5	CW2-60609W
12U	60	40	Single	64	CW1-60412W
	60	50	Double	64	CW2-60512W
	60	60	Double	64	CW2-60612W