


# WALL RACK OUTDOOR



**19"GERMANY**<sup>®</sup>  
EXPORT RACK

## G2 OUTDOOR SERIES



Push Handle Lock



Mounting Pole w/Screen UH



Mounting Pole Can be Adjustable



3 Knock Out Holes

### FEATURES

- ◆ **Designed and Manufactured** To comply with EIA-310-E (Rev.EIA-310D) IEC 60297-1, IEC 60297-2, BS5954 part : 2, DIN 41494, IEC 60529 : 2013 Standard.
- ◆ **19" Wall Rack Type** It was designed for outdoor application and suitable for 19" Standard of Network Equipment, FDU, Patch panel or CCTV system.
- ◆ **Rack unit Size** 6U, 9U or 12U
- ◆ **Dust and Water Protection** Comply to IP55 Standard.
- ◆ **Two Layers Design** Front and side panel provide the sun shield layer for harsh Environment of outdoor application.
- ◆ **Structure** Made from 1.2mm Electro-Galvanized Steel Sheet, light weight and 100% rust proof.
- ◆ **Front Door** Two layers design with push-handle lock and 180° opening door with roofer for ventilation.
- ◆ **Side Panel** Can open both side 120° with push-handle lock for easy installation, water proof, dust filter with roofer for ventilation.
- ◆ **Back Side** Four steel support bar with 2.0mm thickness.
- ◆ **Roof Cover** There is ventilation grill. The top side can be mounted with 1-3 of 4" the ventilating fan to ventilate the accumulated heat inside of the cabinet and extend the lifetime of network equipment.
- ◆ **Waterproof** Front door, Side panel and Roof cover waterproofed by CNC foam gasket sealing
- ◆ **Mounting Pole** Made from 2.0mm Electro-Galvanized Steel with 8 levels adjustable and screened Rack unit (U) on the mounting pole.
- ◆ **Base** Provided removable plate with rubber shield and 3 knock out holes with ¾" and 1" size for cable access.
- ◆ **Grounding System** Provided 3 ground wire connecting point, which connect between cabinet's structure and door.
- ◆ **Color** Special dark gray color painted by Electrostatic powder coat system with international standards ASTM.
- ◆ **Manufacturer and Distributor** Certified by ISO 9001 : 2015.

### ORDERING INFORMATION

W=Width 600 mm. Standard

1U = 44.45 mm.	Overall Height (mm.)	Order No. of Different Depth (mm.)			Color
		D = 400	D = 500	D = 600	
6U	480	G2-60406OUT	G2-60506OUT	G2-60606OUT	Dark Grey
9U	613	G2-60409OUT	G2-60509OUT	G2-60609OUT	Dark Grey
12U	745	G2-60412OUT	G2-60512OUT	G2-60612OUT	Dark Grey

### Recommend Accessories

Order No.	Description	Color
G7-05001	1 x Ø 4" Heavy Duty Fan	Black
G7-05002	2 x Ø 4" Heavy Duty Fan	Black, Light Grey
G7-00006	AC Power Distribution 6 Outlet w/Cable 3M & Surge Protection	Black, Light Grey

