


AC POWER DISTRIBUTION UNIT, 32A



19"GERMANY[®]
EXPORT RACK



32A



IEC 60309




Circuit Breaker



Safety Shutter
TIS Outlet



LED Pilot
Lamp



Surge suppressor
(Line suppression)

FEATURES

- ◆ **Applications** Provided TIS outlet which is suitable for network equipment, computer, etc.
- ◆ **32A AC Power Distribution Unit**
 - 3x6mm² with 32A circuit breaker and surge protector for short circuit protection.
 - 3m Power cord with IEC 60309 plug for 12 and 20 outlets.
- ◆ **19" Germany Export Rack Socket** Made from PC/ABS (UL94V-0), TIS type with embossing trademark.
- ◆ **Manufactured provide**
 - LED Pilot Lamp and 32A Circuit Breaker w/Guard
 - Housing is made from Electro-Galvanized Steel sheet in Light gray or Black paint by Electrostatic powder coating process.
 - Mounting bracket for vertical installation in 19" Rack cabinet.
- ◆ **Manufacturer and Distributor** Certified by ISO 9001 : 2015.

Technical Specification

Socket Outlet	:	Safety Shutter Socket with L, N and G, TIS 166-2549
Circuit Breaker w/Guard	:	32A
Surge Current	:	6.5KA or 10KA
Input Voltage	:	220 - 250VAC, 50/60Hz
Max Power	:	8,000W
Plug Type	:	Power Plug IEC 60309 (32A), IP44
Housing	:	Electro-Galvanized Steel Thickness 0.8mm.
Power Cord	:	VCT-G, TIS 11 Part101-2553
Temperature	:	-25°C to +85°C

ORDERING INFORMATION

Order No.	Description	Figure
G7-00112	AC POWER DISTRIBUTION 12 TIS Outletw/Cable 3 M. & IEC 60309 Plug W/CB 32A	G
G7-00120	AC POWER DISTRIBUTION 20 TIS Outletw/Cable 3 M. & IEC 60309 Plug W/CB 32A	H

* Black Color : G7-00XXXB



GERMAN RACK
2023 -2024

PDU Product Guide

Order Number	Safety Shutter Outlet		Plug Type		Special Function					L x W x H (cm)
	TIS 166-2549	TIS 166-2549 (Black)	TIS 166-2549	Industrial Power Plug IEC60309	Lighting Switch w-Cover	LED Pilot Lamp	Electronic Circuit Breaker	Circuit Breaker w/Guard	Surge suppressor	
G7-00004	4	-	✓	-	✓	-	✓	-	✓	39.2 x 5.8 x 4.45
G7-00006	6	-	✓	-	✓	-	✓	-	✓	49.5 x 5.8 x 4.45
G7-00008	8	-	✓	-	✓	-	✓	-	✓	59.5 x 5.8 x 4.45
G7-00012	12	-	✓	-	✓	-	✓	-	✓	78.4 x 5.8 x 4.45
G7-00020	20	-	✓	-	✓	-	✓	-	✓	118 x 5.8 x 4.45
G7-00004B	-	4	✓	-	✓	-	✓	-	✓	39.2 x 5.8 x 4.45
G7-00006B	-	6	✓	-	✓	-	✓	-	✓	49.5 x 5.8 x 4.45
G7-00008B	-	8	✓	-	✓	-	✓	-	✓	59.5 x 5.8 x 4.45
G7-00012B	-	12	✓	-	✓	-	✓	-	✓	78.4 x 5.8 x 4.45
G7-00020B	-	20	✓	-	✓	-	✓	-	✓	118 x 5.8 x 4.45
G7-00112	12	-	-	✓	-	✓	-	✓	✓	87 x 5.8 x 4.45
G7-00120	20	-	-	✓	-	✓	-	✓	✓	127 x 5.8 x 4.45
G7-00112B	-	12	-	✓	-	✓	-	✓	✓	87 x 5.8 x 4.45
G7-00120B	-	20	-	✓	-	✓	-	✓	✓	127 x 5.8 x 4.45