



PoE Injector

LINK PoE Injector is a 10/100/1000 Base-T single port, high-power PoE solution for remote PD devices. By generating up to 30W, There are supplies remote power for applications such as wireless access points, pan-tilt-zoom (PTZ) IP cameras and IP-Phones. It complies with IEEE802.3af/at PoE+ standards.



PS-8613
Gigabit PoE Injector, 30W



PS-8616
Gigabit PoE Injector, 60W

- 1 x 10/100/1000Mbps RJ45 port
- Delivering power up to 30W (PS-8613) and 60W (PS-8616)
- Support IEEE802.3af/at PoE standard
- Support auto MDI/MDI-X and auto-negotiation
- Automatic detection and protection of non-PoE devices
- 100~240 VAC, 50 to 60 Hz Power Input
- Operating temperature of -10°C to +50°C
- To provide easy installation with plug-and-play

PoE Surge Protector

PoE surge protector is an appliance designed to protect your devices from voltage spikes. It is used for the devices typically installed in outdoor surveillance systems, communications systems and other heavy-duty industrial systems, for the purpose of protecting against electrical surges and spikes, including those caused by lightning.



UT-8006



UT-8010



UT-8022



UT-8088

Part Number		UT-8006	UT-8010	UT-8022	UT-8088
Specifications	Interface	10/100/1000 Base-T	10/100/1000 Base-T	10/100/1000 Base-T	10/100/1000 Base-T
	PoE Standard	IEEE 802.3af/at	IEEE 802.3af/at	IEEE 802.3af/at	IEEE 802.3af/at
	Maximum discharge voltage (Vmax)	6kV	10kV	10kV	20kV
	Max Discharge Current	150A	5kA	2kA	8kA
	Housing	Plastic	Plastic	Aluminum	Aluminum

EoC (Ethernet over Coaxial)

LINK EoC Series is model for Ethernet over Coaxial with PoE standards, fulfill the real time transmission over coaxial. it provides high performance and transmit IP video (2 MP resolution, Full HD) or Ethernet up over existing coaxial. It can reduce the cost by avoid re-cabling when you require to replace IP camera instead analog camera.



PS-0122SET
1-Port FAST EoC w/PoE Converter SET

- 1 x 10/100Mbps RJ45 port and 1 x BNC
- Support IEEE802.3af/at PoE standard
- Support auto MDI/MDI-X and auto-negotiation
- Support Topology with Point to Point and Cascading
- transmit IP video or Ethernet up to 750m at 60Mbps max rate over existing coaxial
- Support to transmit VLAN packets (IEEE802.1Q)
- Operating temperature of -20°C to +70°C



PS-0120T
EoC w/PoE Transmitter



PS-0121R
EoC Receiver



PS-0194
Spare EoC AC Adapter 52V, 2.5A, 130W for EoC Receiver

HDMI Converter

Easy to distribute Full HD video from HDMI source by IP Network with resolution up to 1080p/60p and 100 meter distance over Cat6 cable.



VHD-7311
HDMI to 1-port UTP Transmitter Video Converter



VHD-7311R
UTP to 1-port HDMI Receiver Video Converter



VHD-7312R
UTP to 2-port HDMI Receiver Video Converter

- Easy to distribute Full HD video from HDMI source by IP Network
- Extends the transmission distance up to 100m over Cat6/6A Cable
- Support resolution up to 1080p/60Hz