

# PSG-3104A

## 4-Port Gigabit Ethernet PoE Switch (60W)



### Description



PSG-3104A is an L2 unmanaged PoE switch with 4x10/100/1000Mbps ports, each PoE port allows to supply up to 30W and can supply power for IP Surveillance, VoIP Phone, wireless access point and other power devices. The plug & play technology enable this switch to interact with devices automatically after connected. The switch built-in flow control, it is to improve network performance for SMB applications in offices.

### Features Highlight

- Auto negotiation**  
 PSG-3104A is unmanaged PoE switch and equipped with 5x10/100/1000Base-T, let the small work groups flexibly connected to the Ethernet. These intelligent port automatically detect network speed and automatic negotiation 1000Base-T, 100Base-TX and 10Base-T, as well as the full duplex and half duplex.
- Traffic control safety transmission**  
 All ports support IEEE 802.3x flow control protocol. This function is when the port's receive buffer is full and sent collision signal, it can maximum limit reduce the packet is discarded. It is provided in full duplex and back-pressure flow control in half duplex.
- Automatic MDI/MDI-X**  
 All ports support auto MDI/MDI-X crossover functions. Any port can use normal through twisted-pair cable, easy access to the server or switch.
- PoE Support**  
 To reduce the required time and cost of installing additional electrical sources, the PSG-3104A implements PoE technology. The switch supplies power over the same cable that is used to carry network traffic and delivers a power budget of 140W
- Power adapter**  
 PSG-3104A is using a desktop power supply DC 55V/1.3A, easy to use and there are panel LEDs dynamic display.

### Specifications

Standards	
IEEE 802.3	10Base-T (Ethernet)
IEEE 802.3u	100Base-TX (Fast Ethernet)
IEEE 802.3ab	1000Base-T (Gigabit Ethernet)
IEEE 802.3x	Flow Control (full-duplex flow control)
IEEE 802.3az	Energy-Efficient Ethernet
IEEE 802.3af	Power over Ethernet (PoE)
IEEE 802.3at	Power over Ethernet Plus (PoE+)
Interface	
PoE Ports	4 x 10/100/1000Base-T, RJ45 port
Uplink Port	1 x 10/100/1000Base-T, RJ45 port
LED Panel	PWR, 10/100M, 1000M, PoE, LNK/ACT
Features	
Performance	Switching Capacity: 10Gbps Forwarding Rate: 7.44Mpps Packet Buffer Memory: 1Mbit Jumbo Frame size: 9KBytes MAC Address: 2K Transmission Method: Store and Forward
Features	Layer 2 Switch L2 Unmanaged PoE Switch Flow Control, Auto-Nego, Auto MDI/MDI-X
Power	
PoE Power Budget	60W
Power Adapter	Input: 100-240VAC, 50/60Hz Output: 55VDC/1.3A

Mechanical and Environment	
Operating Temperature	0~40°C
Storage Temperature	-40~70°C
Operating Humidity	10~95% RH (non-condensing)
Storage Humidity	5~95% RH (non-condensing)
Dimension (W x H x D)	121 x 26 x 75 (mm)
Standards and Certifications	
Standards Compliance	FCC Part 15, Subpart B Class A ANSI C63.4-2014 EN55032: 2015+AC:2016 Class A EN55035: 2017 LVD EN62368-1:2014 EN/IEC/UL 60950-1
Green Product	RoHS
Ordering Information	
PSG-3104A	4-Port Gigabit Ethernet PoE Switch

#### Note :

\* Specifications subject to change without notice.

