


LINK Telephone Cable Station Wire (TIEV) is designed and manufactured for connecting subscriber equipment inside the building.



## MECHANICAL SPECIFICATIONS

Conductor	0.5 and 0.65 mm Solid Annealed Copper
Insulation	High density polyethylene (HDPE)
Identification	2 core : Red and Green 4 core : Red, Green Yellow and Black
Sheath	Ivory, Polyvinyl Chloride (PVC)



## ELECTRICAL CHARACTERISTICS

Test Item	Conductor diameter mm. (AWG)	
	0.50 (24)	0.65 (22)
1. Max. Conductor Resistance@ temp 20° C (Ω/km)	92	58
2. Min. Insulation Resistance@ temp 20° C (MΩ/km)	16,000	16,000
3. Dielectric Strength between Conductor, DC at 3sec (kV)	3.0	3.0

## ORDER INFORMATION

LINK P/N	Number of Cores	Conductor diameter		Insulation Thickness (mm.)	Sheath Thickness (mm.)	Overall diameter (mm.)	Packaging
		mm.	AWG				
UL-1022	2	0.50	24	0.20	0.40	2.8	100M./ Easy Box
UL-1024	4	0.50	24	0.20	0.40	3.4	100M./ Easy Box
UL-1024-5	4	0.50	24	0.20	0.40	3.4	500M./ Reelex
UL-1032	2	0.65	22	0.25	0.45	3.4	100M./ Easy Box
UL-1034	4	0.65	22	0.25	0.45	4.0	100M./ Easy Box
UL-1034-5	4	0.65	22	0.25	0.45	4.0	500M./ Reelex