

Category 6A Patch Cords



LINK Category 6A Patch Cords are ANSI/TIA-568.2-D requirement for Category 6A performance. LINK Category 6A Patch Cords are assembled by manufacturer with totally test to reach the standard by Q.C team. LINK Category 6A Patch Cord assembly of high grade of CAT 6A Cable and CAT 6A Pulg with Cover Boot.

SPECIFICATION



Standard : ANSI/TIA-568.2-D Category 6A, ISO/IEC 11801:2017 Class EA,
 Application : 10/100/1000 BASE-T, 2.5G/5G, 10G BASE-T, IEEE 802.3i/u/ab/bz/an, PoE/PoE+, 4/16 Token Ring, 52/155/622Mbps and 1.2Gbps ATM, ISDN, VoIP and other
 Cable : Stranded wire flexible S/FTP category 6A performance
 Flame rating : LSZH
 Color : White, Aqua blue (Available color on request)
 Connector : Category 6A RJ45 modular plug with over 50 micro-inches gold plating
 Wire Size : 26 AWG
 Cover Boot : Transparent boot from manufacturer are designed to protect plugs and cables
 Q.C. : 100% factory assembly and testing
 Approvals : Intertek Channel Test
 Certified : Lead-free & RoHS Compliant



Ex. US-5201SLZ-1 : Shield CAT6A RJ45 to RJ45 Patch Cord, LSZH, White, 1 meter



Ex. US-5201SLZ-9 : Shield CAT6A RJ45 to RJ45 Patch Cord, LSZH, Aqua blue, 1 meter

Part No.	Description	Length (m.)	Color
US-5201SLZ-X	Shielded CAT6A RJ45 to RJ45 Patch Cord, LSZH	1	White, Aqua blue
US-5202SLZ-X	Shielded CAT6A RJ45 to RJ45 Patch Cord, LSZH	2	White, Aqua blue
US-5203SLZ-X	Shielded CAT6A RJ45 to RJ45 Patch Cord, LSZH	3	White, Aqua blue
US-5205SLZ-X	Shielded CAT6A RJ45 to RJ45 Patch Cord, LSZH	5	White, Aqua blue
US-5210SLZ-X	Shielded CAT6A RJ45 to RJ45 Patch Cord, LSZH	10	White, Aqua blue
US-5215SLZ-X	Shielded CAT6A RJ45 to RJ45 Patch Cord, LSZH	15	White, Aqua blue
US-5220SLZ-X	Shielded CAT6A RJ45 to RJ45 Patch Cord, LSZH	20	White, Aqua blue

X Color = 1 (White), 9 (Aqua Blue)

Category 6A In-Line Couplers

LINK In-Line Couplers provide a 180 Jack to Jack Splice. Couplers are available in eight position RJ45 Styles allow a simple operation with horizontal cables, which can easily be extended. Broken cables can be coupled without laying new complete cable segment. LINK In-Line Couplers are universal standards for all RJ45 Modular Plugs.

SPECIFICATION

Standard : ANSI/TIA-568.2-D Category 6A, ISO IEC-11801:2017 Class EA, EN50173-1
 Application : 10/100/1000 BASE-T, 2.5G/5G, 10G BASE-T, IEEE 802.3i/u/ab/bz/an, PoE/PoE+, 4/16 Token Ring, 52/155/622Mbps and 1.2Gbps ATM, ISDN, VoIP and other
 Product Type : RJ45 Jack to RJ45 Jack
 Color : White / Metallic with LINK logo
 Certified : Lead - free & RoHS Compliant



A



B

Part No.	Description	Type	Figure	Dimension (mm.)	Color
US-4007SIL	SHIELD CAT 6A IN-LINE COUPLERS	Shield	A	L 36 x W 17.8 x H 22	Metallic
US-4007IL	CAT 6A IN-LINE COUPLERS	Unshield	B	L 35 x W 16.3 x H 21	White