


- 1. DATA RATES TO 2.048 Mbps.
- 2. 75 Ohm DUAL COAX TO 120 Ohm TWISTED PAIR.
- 3. BI-DIRECTIONAL SIGNAL CONVERSION.
- 4. NO AC POWER OR BATTERIES NEEDED.
- 5. FEMALE COAX BNC CONNECTORS AVAILABLE.

4	1SET	PCB SET(TRANSFORMER 1:1.26 *2,C1 1uF)	
3	1SET	PCB TYPE SHIELDED JACK,GOLD 50u"	GLASS FILLED POLYESTER UL 94V-0
2	1SET	PLASTIC SET (TOP,BOTTOM&SIDE COVER*2)	ABS UL 94V-0
1	2SET	BNC FEMALE SOLDER TYPE	NICKEL(100u"-150u")
ITEN	Q'TY	DESCRIPTION	REMARK


**LINK (FAR-EAST) CORPORATION**

DRAW BY <b>K.Lee</b>		PART No. <b>UT-5012</b>	
APPROVED <b>David</b>		TITLE	
DATE <b>Aug/06/07</b>	SHEET <b>1/1</b>	<b>G.703 BALUN SHIELDED RJ45 JACK TO 2 x FEMALE BNC</b>	
SCALE <b>-</b>	DRAWING No. <b>-</b>		