


TECHNICAL SPECIFICATION:

TRANSMISSION BANDWIDTH DC TO 8MHz
 TRANSMISSION DISTANCE 680M (COLOR : CAT 5)MAX.
 780M (MONOCHROME : CAT 5)MAX.
 INSERTION LOSS < 2dB
 SIGNAL RETURN LOSS ≥ -15dB
 COMMON MODE REJECTION ≥ -40dB
 MAXIMUM INPUT 1.0Vp-p TYP.

4	PCB SET WITH 1 TRANSFORMER			1
3	PCB TYPE RJ45 JACK	ABS(UL94V-0)		1
2	PLASTIC SET (TOP,BOTTOM & SIDE COVER)	ABS(UL94V-0)		1
1	BNC MALE SOLDER TYPE	BRASS FINISH NICKEL		1
NO	DESCRIPTION	MATERIAL	REMARK	Q'TY

		LINK (FAR-EAST) CORPORATION	
DRAW BY K.Lee		PART No. UT-5034	
APPROVED David		TITLE	
DATE Aug/06/07	SHEET 1/1	CCTV (VIDEO) BALUN UNSHIELDED RJ45 JACK TO MALE BNC FOR INDOOR USE (4/-,5/+ or 8/-, 7/+)	
SCALE -	DRAWING No. -		