

SFP 1.25G Transceiver

LINK SFP, SFP+ and QSFP+ transceivers are high performance, cost effective modules which is the best for all LINK Media Converters, all LINK Switches and can be compatible with a wide variety of switches and routers brand.



UT-9125D-XX

SFP 1.25G Transceiver (for Cisco and others brand compatible)

UT-9125DHP-XX

SFP 1.25G Transceiver (for HP, Aruba and 3Com compatible)

- Available distances up to 120km
- Dual data-rate of 1.25Gbps/1.063Gbps operation
- Compliant with Multi-Source Agreement (MSA) and Small Form-factor Pluggable (SFP)
- Compliant with SFF-8472
- Support Digital Diagnostic Monitoring Interface (DDMI)
- Compatible with SONET OC-24-LR-1 and Fibre Channel applications
- Duplex LC connector
- Hot Pluggable
- +3.3V single power supply
- Class 1 laser product complies with EN 60825-1
- Operating temperature of 0°C to +70°C

UT-9113WD-20/UT-9114WD-20

SFP Bi-Di Transceiver (for Cisco and others brand compatible)

UT-9113WDHP-20/UT-9114WDHP-20

SFP Bi-Di Transceiver (for HP, Aruba and 3Com compatible)

- Available distances up to 20km
- Dual data-rate of 1.25Gbps/1.063Gbps operation
- Compliant with Multi-Source Agreement (MSA) and Small Form-factor Pluggable (SFP)
- Compliant with SFF-8472
- Support Digital Diagnostic Monitoring Interface (DDMI)
- Compatible with SONET OC-24-LR-1 and Fibre Channel applications
- Simplex LC connector
- Hot Pluggable
- +3.3V single power supply
- Class 1 laser product complies with EN 60825-1
- Operating temperature of 0°C to +70°C

UT-9125TSD (1000Base-T)

UT-9125T (10/100/1000Base-T)

SFP 1.25G Copper Transceiver (for Cisco and others brand compatible)

- Up to 1.25Gbps bi-directional data links
- Hot-pluggable SFP footprint
- Fully metallic enclosure for low EMI
- Low power dissipation (1.05 W typical)
- Compact RJ-45 connector assembly
- 1000 BASE-T operation in host systems with SERDES interface
- 10/100/1000Mbps compliant in host systems with SGMII interface
- +3.3V single power supply
- Operating temperature of 0°C to +70°C

SFP+ 10G Transceiver



UT-9310A-XX

SFP+ 10G Transceiver (for Cisco and others brand compatible)

UT-9310HP-XX

SFP+ 10G Transceiver (for HP, Aruba and 3Com compatible)

- Available distances up to 80km
- Data Rate up to 10Gbps
- Optical interface compliant to IEEE 802.3ae
- Compliant with Multi-Source Agreement (MSA) and Enhanced Small Form Factor Pluggable (SFP+)
- Compliant with SFF-8472
- Support Digital Diagnostic Monitoring Interface (DDMI)
- Duplex LC connector
- Hot Pluggable
- +3.3V single power supply
- Class 1 laser product complies with EN 60825-1
- Operating temperature of 0°C to +70°C



UT-9402-XX

QSFP+ 40G Transceiver

- Available distances up to 40km
- Delivers reliable 40 GbE connections
- Compliant to IEEE 802.3ba specification for 40GBASE-IR4
- Compliant with Multi-Source Agreement (MSA) and Quad Small Form Factor Pluggable (QSFP+)
- Duplex LC connector
- Hot Pluggable
- +3.3V single power supply
- Class 1 laser product complies with EN 60825-1
- Operating temperature of 0°C to +70°C



UT-9310T

SFP+ 10G Transceiver, 10G Base-T

- Supports Links up to 30m with Cat 6A Cable
- IEEE 802.3az and 802.3an Compliant
- IEEE 802.3bz for 5G & 2.5G BASE-T
- Compliant with Multi-Source Agreement (MSA) and Enhanced Small Form Factor Pluggable (SFP+)
- SFF-8431 and SFF-8432 MSA Compliant
- Compact RJ-45 connector assembly
- Hot Pluggable
- Support MDI/MDI-X
- +3.3V single power supply
- Operating temperature of 0°C to +70°C

XX: The SFP communication distance upon the request (support 550m to 120km).

- SFP support 550m, 10km, 20km, 40km, 80km and 120km.
- SFP+ support 300m, 10km, 40km and 80km.
- QSFP+ support 2km, 10km and 40km